

Product specification sheet

 Prefab concrete kerbs conform EN 1340
 PV – 1340 – 6/2013 - W

 Bleijko Betonindustrie B.V.
 Mariadijk 6a
 4588KJ Walsoorden (NL)

 tel. +31 (0) 114 684000
 fax. +31 (0) 114 682380

 www.bleijko.com
 bleijko@bleijko.com

Fundamental characteristics:

Application	Outer covering
Break resistance	T
Glide and slip resistance	Satisfied
Durability	Satisfied

Director



P. de Beukelaar

Walsoorden, 08-10-2013

Product information

Identification	Band 13/15x25x100 dl
Machine	SOM
Fermentation time	7 days
Class	D – T – H
Appearance	Straight kurb and fittings
Colours	Standard colours
After treatment	-
Weight	88 kg

Supplementary certification

 411/104
 Category Ia

K2066

Characteristics geometric

	Symbols		
	BENOR	KOMO	
Length	l	l	1000 mm
Width above	-	BB	130 mm
Width under	b	BO	150 mm
Width side view	d	-	20 mm
Height	H ₍₁₎	H	250 mm
Height 2	H ₂	-	247 mm
Height side view tot. H ₂	-	-	130 mm
Height side view vert.c	-	-	127 mm
Shampfer	-	-	6/5 mm

